

ECOMUL-II Damp-Proofing Membrane

Is Number ONE When It Comes To Damp-Proofing



A High Quality, High Performance Water-Based Asphalt Emulsion

- Low Viscosity
- High Solids.
- Excellent Ductility.
- Low Penetration.
- Rapid Setting.

COVERAGES

Per Sq.Ft./Gal

Walls - good water protection (10 mils) 120
Walls - better water protection (20 mils) 60

TYPICAL UNCURED PROPERTIES

Specific Gravity (ASTM D 244) 1.000
Viscosity (ASTM D 1200) >25 centipoise
PH 11.5
Flammability (ASTM D 3143) 500°F
Color Brown to black
Non-Toxic No Solvents
Shelf Life 6 months

Packaging

Available in bulk & 275 gal. totes

TYPICAL CURED PROPERTIES

Initial Cure 10 minutes
Final Cure 24-48 hours

EPRO SERVICES
P.O. Box 347
Derby, KS 67037 USA



Phone: 800-882-1896
316-262-2513
Fax: 316-262-2529
Web: www.eproserv.com

ECOMUL-II Specifications

1. PRODUCT NAME

ECOMUL-II

2. MANUFACTURER

EPRO SERVICES
P.O. Box 347
Derby, KS 67037
PHONE 800-882-1896
FAX: 316-794-3451

3. PRODUCT DESCRIPTION

Basic Use: ECOMUL-II is designed to be a basic water protection and vapor retardant barrier for vertical application to both below grade and above grade surfaces. ECOMUL-II is to be applied with a sprayer to produce a rapid curing, monolithic coating. It may be used as a base coat for other water-based products.

Composition: ECOMUL-II is a water-based, medium solids, minutely polymer-modified asphalt emulsion, which exhibits nominal elastomeric qualities to handle minimal expansion and contraction movement and increase its durability.

Benefits:

- VOC compliant.
- Non hazardous, non-toxic, and non-flammable.
- Efficient and effective application.
- Cost effective.
- Non-leaching.
- Excellent dampproofing.

Limitations:

- Should be applied to clean and dry surfaces.
- Adjacent areas and surfaces should be protected from contact with the product.
- Exposure to UV.
- Should be stored above 40°F.
- A test area should always be done to verify compatibility of substrate with product.
- Solvent-based products should not be applied over this product.

4. TECHNICAL DATA

Properties: See chart.

Coverages: See chart.

• Specification Writer:

Contact EPRO Services, L.C. before writing specifications on this project. Test information available upon request.

5. INSTALLATION

Preparation: Must include but not limited to:

- All surfaces should be dry and free of loose materials, release oils and other contaminants. These should be removed prior to application by power washing or other suitable methods.

- Repairs: Any cracks, spall or metal protrusion areas should be repaired by trowel application of ECOLINE-T insuring penetration of materials in damaged or cracked area. Large cracks may also require a layer of fiberglass mesh or polyester mat being spanned over crack and ECOLINE-T applied over this to provide additional membrane strength.

- A test should always be done prior to application using the same cleaning preparation and application procedures to be used on the project.

Application:

- Should be applied in accordance with specific application specifications.
- ECOMUL-II is to be spray applied, which forms a monolithic moisture protection barrier. Spray application produces an approximate 10 mil build on each pass of spray gun.

Cleaning: Clean all tools with kerosene and/or equivalent.

6. AVAILABILITY AND COST:

Contact the local distributor and/or Authorized Applicator for availability and cost.

7. WARRANTY

Limited Warranty: EPRO warrants this product to be free from defects. EPRO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE. EPRO's liability shall be limited in all events to supplying sufficient product to retreat the specific areas to which defective product has been applied. EPRO shall have no other liability, including liability for incidental or resultant damages, whether due to breach of warranty or negligence. This warranty may not be modified or extended by representatives of EPRO or its distributors.

8. MAINTENANCE:

No maintenance required.

9. TECHNICAL SERVICES AND INFORMATION:

Complete technical services and information are available from EPRO Services.



Rev. emII.12.16.02

